

IN THE CLAIMS

For the convenience of the Examiner, all pending claims of the present Application are shown below whether or not an amendment has been made.

Please amend the claims as follows.

1. **(Currently Amended)** A method for processing traffic in an access network, comprising:

receiving a plurality of ingress traffic streams **at a plurality of customer premise equipment (CPE) ports**, each ingress traffic stream including a plurality of packets having a destination address, wherein the packets are Internet Protocol (IP) packets and each include an IP destination address;

segmenting at each CPE port the IP packets in the ingress traffic streams into asynchronous transport mode (ATM) adaption layer (AAL) cells having a fixed ATM address associated with the CPE port, wherein the AAL cells include either or both of a virtual private interface and virtual connection interface (VPI/VCI) ATM address generated from the IP addresses of the IP packets;

aggregating the ingress traffic streams into a single combined traffic stream ~~without regard to any destination of any packet from any ingress traffic stream~~; and

transmitting the combined traffic stream to a backbone network for routing.

2. **(Canceled).**

3. **(Original)** The method of Claim 1, further comprising:

receiving each of the ingress traffic streams from customer premise equipment (CPE);

and

transmitting the combined traffic stream to a backbone router in the backbone network.

4. **(Previously presented)** The method of Claim 1, further comprising:

validating IP packets in the ingress traffic streams; and

aggregating all valid packets into the combined traffic stream.

5. **(Previously presented)** The method of Claim 1, further comprising:
routing IP packets of the ingress traffic streams to a network interface port of an access device; and
aggregating the IP packets into the combined traffic stream at the network interface port.

6. **(Currently Amended)** The method of Claim 1, further comprising:
~~receiving the ingress traffic streams at a plurality of customer premise equipment (CPE) ports;~~
~~segmenting at the CPE ports the IP packets in the ingress traffic streams into asynchronous transport mode (ATM) adaption layer (AAL) cells, wherein the AAL cells include either or both of a virtual private interface and virtual connection interface (VPI/VCI) ATM address generated from the IP addresses of the IP packets;~~
switching the AAL cells to a network interface port;
reassembling the IP packets from the AAL cells at the network interface port; and
aggregating the IP packets into the combined traffic stream.

7. **(Currently Amended)** The method of Claim 6, further comprising:
~~segmenting IP packets at each CPE port into sets of AAL cells having a fixed ATM address associated with the CPE port;~~
buffering the AAL cells at the network interface port based on their ATM addresses;
and
reassembling the IP packets from completed sets of AAL cells.

8. **(Canceled)**

9. **(Original)** The method of Claim 6, wherein the IP packets are segmented into ATM adaption layer five (AAL-5) cells.

10. **(Previously presented)** The method of Claim 1, further comprising:
receiving an egress traffic stream from the backbone network, the egress traffic stream including a plurality of IP packets each having an IP address;
determining a customer premise equipment (CPE) port for each IP packet based on its IP address;
routing the IP packets to their respective CPE ports; and
transmitting the IP packets from the CPE ports to their destination CPEs.

11. **(Original)** The method of Claim 10, further comprising determining the CPE ports for the IP packets using a static routing table.

12. **(Previously presented)** The method of Claim 10, further comprising:
determining an asynchronous transport mode (ATM) address for each IP packet of the egress traffic stream based on its IP address;
segmenting each IP packet into a set of ATM adaption layer (AAL) cells having the ATM address for the IP packet;
switching the AAL cells to their respective CPE ports based on the ATM addresses;
and
reassembling the IP packets from the AAL cells at each CPE port for delivery.

13. **(Original)** The method of Claim 12, further comprising:
buffering the AAL cells at each CPE port based on their ATM addresses; and
reassembling the IP packets from completed sets of AAL cells.

14. **(Previously presented)** The method of Claim 12, wherein the ATM address comprises either or both of a virtual private interface and virtual connection interface (VPI/VCI) address.

15. **(Original)** The method of Claim 12, wherein the IP packets are segmented into ATM adaption layer five (AAL-5) cells.

16. **(Canceled)**

17. **(Canceled)**

18. **(Canceled)**

19. **(Canceled)**

20. **(Currently Amended)** A method for routing traffic in an access network, comprising:

receiving ingress Internet Protocol (IP) packets from customer premise equipment (CPE), each IP packet having an IP address;

receiving egress IP packets from a backbone network for delivery to the CPE;

segmenting the ingress IP packets at a CPE interface of an access network into ingress asynchronous transport mode (ATM) adaption layer (AAL) cells **having a fixed ATM address associated with the CPE port**, wherein the ingress AAL cells include either or both of a virtual private interface and virtual connection interface (VPI/VCI) address generated from the IP addresses of the IP packets;

segmenting the egress IP packets at a network interface into egress AAL cells;

providing the egress AAL cells to the customer premises equipment;

aggregating the ingress AAL cells in the access network into a single combined traffic stream ~~without regard to any destination of any packet from the customer premises equipment.~~

21. **(Original)** The method of Claim 20, wherein the IP packets are segmented into ATM adaption layer five (AAL-5) cells.

22. **(Original)** The method of Claim 20, further comprising reassembling the AAL cells into IP packets at a periphery of the access network.

23. **(Original)** The method of Claim 22, further comprising delineating the IP packets.

24. **(Original)** The method of Claim 22, further comprising validating the IP packets.

25. **(Original)** The method of Claim 22, further comprising dropping defective IP packets.

26. (Currently Amended) A ~~system~~ non-transitory computer readable medium comprising logic for processing traffic in an access network, the logic, when executed by a processor, operable to comprising:

~~logic stored in a computer processable medium; and~~
~~the logic operable to~~

receive a plurality of ingress traffic streams at a plurality of customer premise equipment (CPE) ports, each ingress traffic stream including a plurality of Internet Protocol (IP) packets having an IP address,

segmenting at each CPE port the IP packets in the ingress traffic streams into asynchronous transport mode (ATM) adaption layer (AAL) cells having a fixed ATM address associated with the CPE port, wherein the AAL cells include either or both of a virtual private interface and virtual connection interface (VPI/VCI) ATM address generated from the IP addresses of the IP packets;

aggregate the ingress traffic streams into a combined traffic stream ~~without regard to any destination of any IP packet in any ingress traffic stream~~, and

transmit the combined traffic stream to a backbone network for routing based on the IP addresses.

27. (Canceled)

28. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 26, the logic further operable to transmit the combined traffic stream to a backbone router in the backbone network.

29. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 26, the logic further operable to validate IP packets in the ingress traffic stream and to aggregate all valid packets into the combined traffic stream.

30. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 26, the logic further operable to route IP packets in the ingress traffic streams to a network interface port of an access device and to aggregate the IP packets into the combined traffic stream at the network interface port.

31. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 26, the logic further operable to receive the ingress traffic streams at a plurality of customer premise equipment (CPE) ports, segment at the CPE ports the IP packets in the ingress traffic streams into asynchronous transport mode (ATM) adaption layer (AAL) cells, switch the AAL cells to a network interface port, reassemble the IP packets from the AAL cells at the network interface port and aggregate the IP packets into the combined traffic stream, wherein the AAL cells include either or both of a virtual private interface and virtual connection interface (VPI/VCI) address generated from the IP addresses of the IP packets.

32. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 31, wherein the IP packets are segmented into ATM adaption layer five (AAL-5) cells.

33. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 31, the logic further operable to ~~segment IP packets at each CPE port into sets of AAL cells having a fixed ATM address associated with the CPE port~~, buffer the AAL cells at the network interface port based on their ATM addresses, and reassemble the IP packets from completed sets of AAL cells.

34. (Canceled)

35. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 26, the logic further operable to receive an egress traffic stream from the backbone network, the egress traffic stream including a plurality of IP packets each having an IP address, determine a customer premise equipment (CPE) port for each IP packet based on its IP address, route the IP packets to their respective CPE ports and transmit the IP packets from the CPE ports to their destination CPEs.

36. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 35, the logic further operable to determine the CPE ports for the IP packets using a static routing table.

37. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 35, the logic further operable to determine an asynchronous transport mode (ATM) address for each packet based on its IP address, segment each IP packet into a set of ATM adaption layer (AAL) cells having the ATM address for the IP packet, switch the AAL cells to their respective CPE ports based on the ATM addresses and reassemble the IP packets from the AAL cells at each CPE port for delivery based on their IP addresses.

38. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 37 the logic further operable to buffer the AAL cells at each CPE port based on their ATM addresses and reassemble the IP packets from completed sets of AAL cells.

39. (Canceled)

40. (Currently Amended) The ~~system~~ non-transitory computer readable medium of Claim 37, wherein the IP packets are segmented into ATM adaption layer five (AAL-5) cells.